## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark	: Wiz
-------------------------------	-------

Supplier's address: WiZ, WiZ I.B.R.S. / C.C.R.I. Number 10461, 5600VB Eindhoven, NL

Model identifier: 9290035000W

_	•			
Type	Λt	liaht	COLL	rca.
IVDE	VI.	HEIIL	SOU	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## **Product parameters**

Product parameters				
Parameter		Value	Parameter	Value
	General product parameters:			
<u> </u>	mption in on- 00 h), rounded st integer	19	Energy efficiency class	Е
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone arrow cone (90º)	2 452 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22006500
On-mode pov pressed in W	ver (P <sub>on</sub> ), ex-	18,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, (	tandby power expressed in W the second dec-	0,49	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90
Outer dimen-	Height	163	Spectral power dis-	See image
sions without	Width	83	tribution in the	in last page
separate control gear, light-	Depth	83	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equival	ent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	150	
			Chromaticity coordi-	0,382	
			nates (x and y)	0,380	
Parameters for LED and OLED light sources:					
R9 colour rende	ring index value	0	Survival factor	0,90	
the lumen maintenance factor		0,93			
Parameters for	Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that an I replaces a flu source without last of a particul	orescent light integrated bal-	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,9	

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

